Case Study

GORE® LOW DRAG Filter Bags – Reducing Differential Pressure in Carbon Black

Challenge

One of the most important metrics for a baghouse is differential pressure (dP). A consistently high dP indicates blinding of the filter media and/or poor release of dust cake during cleaning, typically leading to lower airflow (throughput), throttling back of production rates and shorter bag life.

A carbon black manufacturer faced the need to lower dP in the baghouse in order to increase airflow through the reactor — and, as a result, increase production. The manufacturer also wanted to extend the service.

Solution

The customer replaced its traditional membrane filter bags with GORE LOW DRAG Filter Bags. These filters incorporate a proprietary ePTFE advanced membrane whose cleanable surface results in lower baghouse dP and increased airflow. The decreased dP enables the operator to increase gross filtration time and reduce cleaning frequency, which in turn decreases the stress on the filter bags and leads to longer bag life.

Results

The figures show the measured dP (in Pa) of two compartments in the customer's baghouse, one containing a traditional ePTFE membrane bag (black) and the second containing GORE LOW DRAG Filter Bags (red). The data show that the dP in the baghouse with GORE LOW DRAG Filter Bags is 15–20% lower on average during both filtration and cleaning cycles. This lower dP has persisted even after one year of service, and is consistent across multiple carbon black grades.



Application Carbon black

(main unit filter/reactor filter)

Temperature 220 °C – 260 °C

Flow rate 35,000 Am³/hr

Filtration Area 972 m² **Baghouse Type** Reverse air


Filter material GORE LOW DRAG Filter Bags


(Acid Resistant 339 gsm Fiberglass

Fabric)



Baghouse with GORE LOW DRAG Filter Bags: dp is 15-20% lower on average during both filtration and cleaning cycles





GORE LOW DRAG Filter Bags

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

All technical information and advice given here are based on Gore's previous experiences and/or test results. Gore gives this information to the best of its knowledge, but assumes no legal responsibility. Customers are asked to check the suitability and usability in the specific application, since the performance of the product can only be judged when all necessary operating data are available. The above information is subject to change and is not to be used for specification purposes. Gore's terms and conditions of sale apply to the sale of the products by Gore.

GORE, Together, improving life and designs are trademarks of W. L. Gore & Associates. © 2022 W. L. Gore & Associates, Inc.